

## Data sheet for three-phase Squirrel-Cage-Motors

三相异步鼠笼电动机数据表

MLFB-Ordering data: YE3-200L-30kW-4



### Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>s</sub> /I <sub>N</sub>	M <sub>s</sub> /M <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub>	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>s</sub> /I <sub>N</sub>	T <sub>s</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	
380	D	50	30	/	56.6	1475	194.2	93.6	93.3	/	0.86	/	/	7.2	2.2	2.5	IE3
660	Y	50	30	/	32.6	1475	194.2	93.6	93.3	/	0.86	/	/	7.2	2.2	2.5	IE3
IM B3			FS 2 0 0 L			240kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

### Mechanical data / 机械性能数据

Sound pressure level 50Hz/60Hz (No load) 声压等级 50Hz/60Hz (空载)(dB(A))	83/88
Moment of inertia 转动惯量 (kgm <sup>2</sup> )	0.2821
Bearing DE   NDE 轴承 DE   NDE	6312 C3   62 12 C3
Relubrication quantity (DE NDE) 再润滑用量 (g) (DE NDE)	30   30
Relubrication interval (DE NDE) 再润滑周期 (h) (DE NDE)	2000
Lubricants 润滑脂	长城BME
Regreasing device 再润滑装置	Yes
Grease nipple 油杯	M10x1
Type of bearing 轴承类型	Fixed bearing on NDE
Condensate drainage holes 排水孔	No
External earthing terminal 外部接地	No
Vibration class 振动等级	A
Insulation 绝缘等级	155(F)
Duty type 工作方式	S1
Direction of rotation 旋转方向	Bidirectional
Frame material 机座材料	Cast iron
Data of anti condensation heating 防潮加热	No
Coating 喷漆	Yes
Color 颜色	B01
Motor protection 电机保护	A = Without winding protection
Method of cooling 冷却方式	IC411 - Self ventilated, surface cooled

### Terminal box / 接线盒

Terminal box position 接线盒位置	Top
Material of terminal box 接线盒材料	Steel
Type of terminal box 接线盒型号	/
Cable diameter 电缆直径 (mm)	22-32
Max. cross-sectional area 最大电缆截面积 (mm <sup>2</sup> )	/
Main terminal thread 接线端子螺纹	6xM8
Cable gland 葛兰	2 gland
Main cable entry 主进线孔螺纹规格	2xM48x2

### Special design / 特殊设计

### Environmental conditions / 环境条件

Ambient temperature 环境温度(°C)	-15 ~ 40
Altitude above sea level 海拔高度	1000m