

Data sheet for three-phase Squirrel-Cage-Motors

三相异步鼠笼电动机数据表

MLFB-Ordering data: YE3-355L-315kW-2



Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U	D / Y	f	P	P	I	n	M	NOM. EFF at ... load [%]			Power factor at ... load			I _s /I _N	M _s /M _N	M _k /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _s /I _N	T _s /T _N	T _B /T _N	
380	D	50	315	/	549	2980	1009	95.8	96.0	/	0.91	/	/	7.2	2.0	2.3	IE3
660	Y	50	315	/	316	2980	1009	95.8	96.0	/	0.91	/	/	7.2	2.0	2.3	IE3
IM B3			FS 3 5 5 L			1750kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Mechanical data / 机械性能数据

Sound pressure level 50Hz/60Hz (No load)	100/105
声压等级 50Hz/60Hz (空载)(dB(A))	
Moment of inertia	3.2298
转动惯量 (kgm ²)	
Bearing DE NDE	6317 C3
轴承 DE NDE	63 17 C3
Relubrication quantity (DE NDE)	50
再润滑用量 (g) (DE NDE)	50
Relubrication interval (DE NDE)	2000
再润滑周期 (h) (DE NDE)	
Lubricants	长城BME
润滑脂	
Regreasing device	Yes
再润滑装置	
Grease nipple	M10x1
油杯	
Type of bearing	Fixed bearing on NDE
轴承类型	
Condensate drainage holes	No
排水孔	
External earthing terminal	No
外部接地	
Vibration class	A
振动等级	
Insulation	155(F)
绝缘等级	
Duty type	S1
工作方式	
Direction of rotation	Bidirectional
旋转方向	
Frame material	Cast iron
机座材料	
Data of anti condensation heating	No
防潮加热	
Coating	Yes
喷漆	
Color	B01
颜色	
Motor protection	A = Without winding protection
电机保护	
Method of cooling	IC411 - Self ventilated, surface cooled
冷却方式	

Environmental conditions / 环境条件

Ambient temperature	-15 ~ 40
环境温度(°C)	
Altitude above sea level	1000m
海拔高度	

Terminal box / 接线盒

Terminal box position	Top
接线盒位置	
Material of terminal box	Steel
接线盒材料	
Type of terminal box	/
接线盒型号	
Cable diameter	44-57
电缆直径 (mm)	
Max. cross-sectional area	/
最大电缆截面积 (mm ²)	
Main terminal thread	6xM16
接线端子螺纹	
Cable gland	2 gland
葛兰	
Main cable entry	2xM72x2
主进线孔螺纹规格	

Special design / 特殊设计